

Multifunctional Asphalt Concrete Paver

SRP90S PLUS

Multifunctional Asphalt Concrete Paver

- ▶ Engine model: BF6M1013-22T3R/SC9DK220.1G3
- ▶ Rated power: 159 kW/2000 rpm/ 162 kW/2000 rpm
- ▶ Total weight: 24 t

Product features

SRP90S PLUS multifunctional paver is a professional equipment used in asphalt concrete surface and base stabilized material paving of highway and other types of road. It is driven by hydraulic force and controlled by microcomputer; screed plate adopts double vibrating and eccentric vibratory compaction technology; material level adopts ultrasonic sensing control technology. This makes the paver have advantage of good paving stability, even material separating and feeding, high prepressing density, smooth surface and easy to operate. Therefore the SRP90S PLUS paver is an ideal construction machine for base and surface paving projects and it offers superior paving performance to maximize productivity while providing exceptional reliability.



shantui e-shop

SHANTUI

VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:

No. 58, G327 Highway
Jining City, Shandong, CHINA

TEL: +86-537-2909369

FAX: +86-537-2311219

EMAIL: trade@shantui.com

SRP90S PLUS

Technical specifications:

SRP90S PLUS

Item		Unit	Basic parameters	
Basic paving width		m	3-5.7	
Max. paving width			9	
Max. paving thickness		mm	350	
Paving speed		m/min	0-18	
Traveling speed		Km/h	0-2.4	
Hopper capacity		t	15	
Theoretical productivity		t/h	850	
Camber adjustment		%	-1-+3%	
Gradeability		%	20	
Longitudinal evenness		mm/3m	<2	
Cross slope error		%	±0.02	
Compactedness inhomogeneity		%	<5	
Lubricating type			Central lubrication	
Heating type			electrical heating type	
Diesel engine	Model		BF6M1013-22T3R	SC9DK220.1G3
	Power /RPM	KW/r/min	159/2000	162/2000
Screed	Vibration speed		0-1470	
	Vibration travel	Main	mm	4
		Assist		4
Vibration frequency		Hz	0-50	
Vehicle weight	Total weight		24	
	Weight at max. working status		30	
Overall dimension LxBxH		mm	7800×9000×3360	
Transportation dimension LxBxH			7800×3000×3800	

► THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.